

NAME

2do - simple 2do list manager

SYNOPSIS

2do [-c] *file* [*nr...* | *task...*]

DESCRIPTION

2do is a trivial 2do list manager that stores 2do lists in `$HOME/.2do`. If no options are given, *2do* will print all available lists. If just one argument is given, it will be taken as the name of which 2do list to print, each task will be given an ID number. If you supply 2do with one or more numbers, separated by space, following the list name, these will be taken as task id's to remove from that list. The `-c` flag will clear all contents in the specified 2do list. Finally, if you add more than one argument string, the first will be taken as the 2do list name, all the rest will be added to the 2do list as a new task.

EXAMPLE

```
for thing in eggs milk cheese; do 2do buy $thing; done
2do buy
1: eggs
2: milk
3: cheese
2do buy 1 3
2do buy
1: milk
```

The script is intentionally basic, there is no support for timestamps, tags or priorities. But its easy enough to add such functionality if you need it.

BUGS

If the list you specified doesn't exist, it will be created. Whether you view this as a bug or a feature depends on how many typos you make.

The task id numbers change when you remove tasks from the list.

Permanently removing a list must be done manually (see *rm(1)*)

SEE ALSO

calendar(1), *ckbox(1)*, *que(1)*, *bm(1)*